

EDDYCUS® PRO-II ECA


EDDY-CURRENT ARRAY INSPECTION SYSTEM FOR CARBON FIBER MATERIALS

The high-frequency eddy-current array system utilizing EddyCus® Pro II series can solve many NDT problems. This powerful and modular system is especially suitable for integration into a production line for automatic inline non-destructive inspection of flat materials. It measures contactless without damaging the material and acquires integral information of the conductivity state in real time while maintaining high resolution. This performance is possible by combining several eddy current channels with sensor-integrated multiplexers and a powerful edge server for data analysis.

The system can be used to characterize individual layers of carbon fiber and thin layers regarding layer thickness, electrical resistance, and other quality properties.


Applications

- Inline production monitoring up to 101" width during the production of NCF plies (gaps, undulations, ply build-up, inclusion of foreign material) especially in hidden and non-visible layers
- Inline monitoring of layer and wall thicknesses and electrical layer resistance of high and low conductive layers on wafers, battery-foils, conductive coatings on glass and plastic in nanometer resolution



Characteristics

- Cascadable system with channel multiplex rate of up to 100 KS/s
- Consisting of 4 EddyCus® Pro II devices and 12 array sensors
- Up to 25 MHz eddy-current excitation frequency with integrated multiplexer
- Maximum pixel resolution: 0.853 mm
- ATEX-compliant for zone 21
- Temperature compensation
- Data analysis and system control through included edge server
- Optional Ethernet-based OPC-UA for smart factory applications
- Analogue and digital I/O for communication with production line
- Algorithms for automated calibrations especially for inhomogeneous and anisotropic materials like NCF (Non-Crimp-Fabrics)



1 Possible defects during NCF production.

2 101" width eddy-current C scan.

3 EddyCus® Pro II ECA measurement bar for 101" inspection width, stacked sensor arrays.

Fraunhofer Institute for Ceramic Technologies and Systems IKTS

Maria-Reiche-Strasse 2
01109 Dresden, Germany

Contact

M.Sc. (NDT) Martin Schulze
Phone +49 351 88815-628
martin.schulze@ikts.fraunhofer.de

www.ikts.fraunhofer.de

Category	Characteristics	Value
General	Dimensions (L, W, H)	5500 x 2220 x 300 mm
	Weight	270 kg
	Operating temperature and humidity range	5...50 °C @ 75 % relative humidity (non-condensing)
	Maintenance	sensor detachable from stand
Interface	Power supply	230 V AC, max 500 W
	Pressured air requirement	4 bar – 10 bar
	Trigger input	incremental encoder input
Measurement system	Eddy-Current channels	4*
	Signal frequency	up to 25 MHz
	Analog gain	20 dB to 60 dB
	Array sensors	12 @ 101" inspection width*
	Vertical sensor channels	256 per array, 3072 in total*
	Horizontal sensor channels	64 per array, 768 in total*
	Image resolution	0.853 mm in width
	Inspection speed	6 m/min at max. resolution, higher speeds possible if lower resolution suffices*
	Gaps / overlaps of NCF plies	+ - 0.25 mm accuracy
Testing capabilities	Angular orientation of NCF plies	+ - 0.1 ° accuracy
	Undulations, plie build-ups and other anomalies in NCF plies	detectable above 1 cm ²
	Foreign object (metallic) in low conductive materials	detectable above 0.25 mm ²
	Layer and wall thickness of thin films	10 nm – 10 µm accuracy, depending on conductivity of material
	Additional inspection tasks	can be developed on customer request

Edge server	Dimensions (L, W, H)	600 x 800 x 2000 mm standard control cabinet
Hardware	High performance 8-core industry PC, 32 GiB RAM, SSD drive*	
Connection to measurement system	Ethernet, +24 V DC	
Storage for measured data	network drive, S3*	
Interface for factory integration (optional)	OPC-UA	
Options for communication with production line	digital I/O, OPC-UA, Ethernet-based communication*	
Software	Windows-based software which controls the system, runs data analysis and stores results, can also be used for offline analysis	
Support for different measurement profiles	from which up to 4 can be used at the same time	
Creation of analysis PDF reports		
Managed .NET SDK based on .NET 4.8 available which may be used for custom applications		
System conformity	The EddyCus® PRO II system meets all relevant requirements of DIRECTIVE 2014/34/EU	
	ATEX Zone 21 compliant	

* The given values can be tailored to meet the customers' requirements.



Disclaimer

Distribution and copying of this document, utilization and reporting of its contents are prohibited – even in parts – if not explicitly allowed. Violation commits to amends.

All rights reserved, especially if a patent is assigned or a trademark is registered.